

model	outlet(inch)	Q(m3/h)	H(m)	Power(kw)	Phase	Qmax.(m3/h)	Hmax.(m)	Weight(kg)	Size
									cm
50GNWQD10-10-0.75	2"	10	10	0.75	1	20	15	23.55	48x20x22
50GNWQD7-15-1.1	2"	7	15	1.1	1	22	16	23.7	48x20x22
50GNWQD15-15-1.5	2"	15	15	1.5	1	30	20	37.25	55x26x25
65GNWQD25-10-1.5	2.5"	25	10	1.5	1	35	18	37.8	55x26x25
50GNWQ10-10-0.75	2"	10	10	0.75	3	20	15	22.35	48x20x22
50GNWQ7-15-1.1	2"	7	15	1.1	3	22	16	23.45	48x20x22
50GNWQ15-15-1.5	2"	15	15	1.5	3	30	20	36.1	55x26x25
65GNWQ25-10-1.5	2.5"	25	10	1.5	3	35	18	36.5	55x26x25
50GNWQ9-22-2.2	2"	9	22	2.2	3	35	24	40.1	61x29x29
65GNWQ20-18-2.2	2.5"	20	18	2.2	3	36	21	41.4	61x29x29
80GNWQ45-9-2.2	3"	45	9	2.2	3	45	17	43.4	61x29x29
50GNWQ15-22-3	2"	15	22	3	3	40	25	45.8	63x26x30
65GNWQ35-15-3	2.5"	35	15	3	3	50	22	46.6	63x26x30
80GNWQ43-13-3	3"	43	13	3	3	65	19	47.4	63x26x30
50GNWQ15-25-4	2"	15	25	4	3	68	29	52	64x29x32
65GNWQ26-22-4	2.5"	26	22	4	3	60	28	52.2	64x29x32
80GNWQ45-17-4	3"	45	17	4	3	76	25	53.9	64x29x32
100GNWQ65-12-4	4"	65	12	4	3	85	23	54.5	64x29x32
65GNWQ30-25-5.5	2.5"	30	25	5.5	3	80	31	61	73x29x32
80GNWQ45-20-5.5	3"	45	20	5.5	3	90	29	62.15	73x29x34
100GNWQ65-16-5.5	4"	65	16	5.5	3	115	27	63.6	73x29x34
65GNWQ20-30-7.5	2.5"	20	30	7.5	3	100	33	70	73x31x35
80GNWQ45-25-7.5	3"	45	25	7.5	3	100	33	72	73x31x35
100GNWQ60—22-7.5	4"	60	22	7.5	3	140	32	73	73x31x35
100GNWQ100-15-7.5	4"	100	15	7.5	3	150	32	73	73x31x35