

model	inlet/outlet	Q	H	Power	speed	efficiency	NPSHr	suction height	suction time	weight
	mm	m3/h	m	kw	rpm	%	m	m	min/5m	kg
25ZWL8-15	25	8	15	2.2	2900	45	2	5.5	3	100
32ZWL5-20	32	5	20	2.2	2900	45	2.5	5.5	3	100
32ZWL10-20	32	10	20	2.2	2900	45	2.5	5.5	3	100
32ZWL9-30	32	9	30	3	2900	48	2.5	5.5	3	120
40ZWL10-20	40/32	10	20	2.2	2900	45	2.5	5.5	3	100
40ZWL20-15	40/32	20	15	2.2	2900	45	2.5	5.5	3	100
40ZWL15-30	40/32	15	30	3	2900	48	2.5	5.5	3	120
50ZWL10-20	50/40	10	20	2.2	2900	45	2.5	5.5	3	100
50ZWL20-12	50/40	20	12	2.2	2900	45	2.5	5.5	3	100
50ZWL20-15	50/40	20	15	2.2	2900	45	2.5	5.5	3	100
50ZWL15-30	50/40	15	30	3	2900	48	2.5	5.5	3	120
50ZWL20-35	50/40	20	35	5.5	2900	48	2.5	5.5	3	150
65ZWL30-18	65/50	30	18	4	1450	45	2.5	5.5	3	200
65ZWL30-18	65/50	30	18	4	2900	45	3	5.5	3	165
65ZWL25-30	65/50	25	30	5.5	2900	50	3	5.5	3	200
65ZWL25-40	65/50	25	40	7.5	2900	50	3	5.5	2	200
65ZWL40-25	65/50	40	25	7.5	1450	50	3	5.5	2	330
65ZWL40-25	65/50	40	25	7.5	2900	50	3	5.5	2	200
65ZWL65-25	65/50	65	25	11	2900	52	3	5.5	2	240
80ZWL40-16	80/65	40	16	4	1450	50	3	5	3	240
80ZWL40-16	80/65	40	16	4	2900	50	3	5	3	165
80ZWL40-25	80/65	40	25	7.5	1450	50	3	5.5	2	330
80ZWL40-25	80/65	40	25	7.5	2900	50	3	5.5	2	200
80ZWL25-40	80/65	25	40	7.5	2900	50	3	5.5	2	200
80ZWL65-25	80/65	65	25	11	2900	52	3	5.5	2	240
80ZWL80-35	80/65	80	35	15	1450	50	3	5.5	2	450
80ZWL80-35	80/65	80	35	15	2900	45	3	5.5	3	285
80ZWL50-60	80/65	50	60	22	2900	55	3	5	3	340
100ZWL100-15	100/80	100	15	7.5	1450	50	4	5.5	3	300
100ZWL80-20	100/80	80	20	7.5	1450	53	4	5.5	3	300
100ZWL100-20	100/80	100	20	11	1450	53	4	5.5	3	340
100ZWL100-30	100/80	100	30	22	1450	53	4	5.5	2	530
100ZWL100-30	100/80	100	30	22	2900	53	4	5.5	2	410
100ZWL80-45	100/80	80	45	30	2900	58	4	5.5	2	480
100ZWL80-60	100/80	80	60	37	2900	58	4	5.5	2	550
100ZWL80-80	100/80	80	80	45	2900	58	4	5.5	2	600
125ZWL120-20	125/100	120	20	15	1450	55	4.5	5.5	2	500
150ZWL180-14	150/125	180	14	15	1450	60	5	5.5	3.5	500
150ZWL180-20	150/125	180	20	22	1450	60	5	5	3	570
150ZWL200-15	150/125	200	15	22	1450	60	5	5	3	570
150ZWL200-20	150/125	200	20	22	1450	60	5	5	3	570
150ZWL200-28	150/125	200	28	30	1450	60	5	5	3	630
150ZWL180-30	150/125	180	30	37	1450	65	5	5	3	680
150ZWL180-38	150/125	180	38	55	1450	45	5	6	3.5	800
150ZWL180-40	150/125	180	40	55	1450	45	5	6	3.5	800
200ZWL280-14	200/150	280	14	22	1450	65	5	5	3	700
200ZWL280-20	200/150	280	20	37	1450	65	5	5	3	780

200ZWL280-28	200/150	280	28	55	1450	55	4	5.2	3	940
200ZWL300-18	200/150	300	18	37	1450	55	4	5.2	3	780
200ZWL300-25	200/150	300	25	45	1450	51	5	5.2	3	948
250ZWL420-20	250/200	420	20	55	1450	61	6	4.5	2.5	1150
250ZWL400-22	250/200	400	22	55	1450	61	6	4.5	2.5	1150
300ZWL800-14	300/250	800	14	55	1450	65	6	4.5	2.5	1400